

To The Point About The Safe Use and Operation of Order Selectors

ANSWERS TO THE REVIEW QUIZ

1. a
2. a
3. b
4. a
5. a
6. a
7. b
8. b
9. a
10. a

To The Point About The Safe Use and Operation of Order Selectors
REVIEW QUIZ

Name _____ Date _____

The following questions are provided to determine how well you understand the information presented in this program.

1. The operator's platform is covered by an overhead guard that provides protection from overhead hazards and falling objects.
 - a. True
 - b. False

2. The service brake pedal, also known as the "dead man's switch," must remain depressed for the order selector to operate.
 - a. True
 - b. False

3. Driving an order selector is just like driving an automobile. The steering and handling characteristics are the same.
 - a. True
 - b. False

4. When driving in reverse, the drive wheel is in the rear and the forks are leading and will swing wide while turning. This wide swinging movement requires extra caution to avoid collisions when turning near objects or pedestrians.
 - a. True
 - b. False

5. Always sound the horn and look around for pedestrians or other hazards prior to moving the order selector.
 - a. True
 - b. False

6. To maximize stability, an order selector should come to a complete stop before raising or lowering the platform, and best practice is to fully lower the platform before traveling.
 - a. True
 - b. False

7. If an item on the inspection checklist is not working correctly, make a mental note of it and then report it after your shift.
 - a. True
 - b. False

8. If it is not possible to safely reach an item, step out onto the racks to get it.
 - a. True
 - b. False

9. When loading the pallet, work from the outside in, starting with the lightest items to be picked. The heaviest items should be placed near the operator's platform to maximize stability.
 - a. True
 - b. False

10. Position the lift close to the rack so items may be obtained without overreaching. Bring the item close to your body, near waist level before lifting.
 - a. True
 - b. False